



**Legend:**

- A - POWER CONNECTOR
  - B - USB [TOUCH RESERVED] [\*]
  - C - DVI-D
  - D - VGA
  - E - OSD KEYBOARD
- [\*] WHEN THE TOUCHSCREEN IS PRESENT

**Display:**

- TFT type : 17" color TFT LED with LED Inverter
- Resolution : 1280x1024 pixel
- Brightness : 250 cd/m<sup>2</sup> (typical)
- Contrast ratio : 1000:1 (typical)
- View angle : -85~80 (H); 88~85 (V)
- Max colours : 16.7 Millions
- Touch type : five wires resistive (optional)

**Generic specifications:**

- Dimension : 382x338x59 ( L x H x W )
- Weight : 4,5 Kg
- Materials : anodized aluminium (panel)  
galvanized (case)
- Protection grade : IP 66 (frontal)
- Mounting type : panel mounting with pins or VESA 100
- Operating temperature : 0 °C - +50 °C (95% humidity, no condensing)

**Input / Output connectors:**

- USB ports : 1x USB 2.0 port [touchscreen reserved, if present]
- Video In : 1x VGA [female] connector  
1x DVI-D connector
- Power connection : 24 VDC terminal block (1x 3-pins)  
110 – 230 VAC standard cable

**Order options:**

- Five wires resistive touchscreen
- Five wires resistive touchscreen with Glass-Film-Glass technology

**Power specification:**

- Rated input voltage : 24 VDC 110 – 230 VAC
- Input voltage limit : 16.....27 VDC 90.....264 VAC
- Power consumption : 20 W (typical consumption)