



Legend:

- | | |
|--------------------------|----------------------------|
| A - POWER CONNECTOR | D - VGA |
| B - USB [TOUCH RESERVED] | E - USB 2.0 [FRONTAL PORT] |
| C - DVI-D | F - OSD KEYBOARD |

Display:

- TFT type : 17" color TFT LED with LED Inverter
- Resolution : 1280x1024 pixel
- Brightness : 250 cd/m² (typical)
- Contrast ratio : 1000:1 (typical)
- View angle : -85~80 (H); 88~85 (V)
- Max colours : 16.7 Millions
- Touch type : five wires resistive

Generic specifications:

- Dimension : 483x356x59 (L x H x W)
- Weight : 5 Kg
- Materials : anodized aluminium (panel)
: galvanized (case)
- Protection grade : IP 66 (frontal)
- Mounting type : rack mounting (9 units)
: fixing holes system
- Operating temperature : 0 °C - +50 °C (95% humidity, no condensing)

Input / Output connectors:

- USB ports : 1x USB 2.0 port [frontal]
: 1x USB 2.0 port [touchscreen reserved]
- Video In : 1x VGA [female] connector
: 1x DVI-D connector
- Power connection : 24 VDC terminal block (1x 3-pins)
: 110 – 230 VAC standard cable

Order options:

- Five wires resistive touchscreen (serial interface)
- Five wires resistive touchscreen with Glass-Film-Glass technology

Power specification:

- Rated input voltage : 24 VDC 110 – 230 VAC
- Input voltage limit : 16.....27 VDC 90.....264 VAC
- Power consumption : 20 W (typical consumption)