



Legend:

- | | |
|--------------------------|-------------------------------------|
| A - POWER CONNECTOR | D - VGA |
| B - USB [TOUCH RESERVED] | E - USB 2.0 [FRONTAL PORT RESERVED] |
| C - DVI-D | F - OSD KEYBOARD |

Display:

- TFT type : 12.1" Color TFT LCD with LED Inverter
- Resolution : 800x600 pixel or 1024x768
- Brightness : 450 cd/m² or 500 cd/m² (typical)
- Contrast ratio : 700:1 (typical)
- View angle : -80~80 (H); 65~75 (V) | -80~80 (H); 80~80 (V)
- Max colours : 16.7 Millions
- Touch type : Five wires resistive

Generic specifications:

- Dimension : 335x270x52 (L x H x W)
- Weight : 3 Kg
- Materials : white anodized aluminium (panel)
galvanized (case)
- Protection grade : IP 66 (frontal)
- Mounting type : panel mount with retaining clips or VESA 100
- Operating temperature : 0 °C - +50 °C (80% humidity, no condensing)

Input / Output connectors:

- USB ports : 1x USB 2.0 port [frontal]
1x USB 2.0 port [touchscreen reserved]
- Video In : 1x VGA [female] connector
1x DVI-D connector
- Power connection : 24 VDC terminal block (1x 3-pins)

Order options:

- Five wires resistive touchscreen
- Five wires resistive touchscreen with Glass-Film-Glass technology
- External 110 – 230 VAC power supply

Power specification:

- Rated input voltage : 24 VDC
- Input voltage limit : 16.....27 VDC
- Power consumption : 14 W (typical consumption)