



**Legend:**

- |                          |                                     |
|--------------------------|-------------------------------------|
| A - POWER CONNECTOR      | D - VGA                             |
| B - USB [TOUCH RESERVED] | E - USB 2.0 [FRONTAL PORT RESERVED] |
| C - DVI-D                | F - OSD KEYBOARD                    |

**Display:**

- TFT type : 15" Color TFT LCD with LED Inverter
- Resolution : 1024x768 pixel
- Brightness : 500 cd/m<sup>2</sup> (typical)
- Contrast ratio : 1500:1 (typical)
- View angle : -85~85 (H); 85~85 (V)
- Max colours : 16.7 Millions
- Touch type : Five wires resistive

**Generic specifications:**

- Dimension : 390x315x52 ( L x H x W )
- Weight : 4 Kg
- Technology construction : true flat
- Materials : anodized aluminium (panel)  
: galvanized (case)
- Protection grade : IP 66 (frontal)
- Mounting type : panel mount with retaining clips or VESA 100
- Operating temperature : 0 °C - +50 °C (80% humidity, no condensing)

**Input / Output connectors:**

- USB ports : 1x USB 2.0 port [frontal]  
: 1x USB 2.0 port [touchscreen reserved]
- Video In : 1x VGA [female] connector  
: 1x DVI-D connector
- Power connection : 24 VDC terminal block (1x 3-pins)

**Order options:**

- External 110 – 230 VAC power supply

**Power specification:**

- Rated input voltage : 24 VDC
- Input voltage limit: : 16.....27 VDC
- Power consumption : 15 W (typical consumption)