


Legend:

- | | |
|------------------------------|---------------------------------|
| A - POWER CONNECTOR | H - USB 2.0 |
| B - RS-232/422/485 [COM 1] | L - RS-232 [COM 4] |
| C - 2x GIGABIT LAN | M - RS-232 [COM 3] |
| D - 2x DP | N - RS-232 [COM 2] |
| E - 4x USB 3.0 | O - C-FAST READER OPTIONAL |
| F - GIGABIT LAN 3 [OPTIONAL] | P - REMOVABLE HD/SSD [OPTIONAL] |
| G - USB 2.0 | |



System:

- CPU : Intel Core i5-6300U 2.4 GHz, Intel Core i7-6600u 2.6 GHz
- Chipset : Intel Core i3-6100U 2.3 GHz
- Graphics : Intel Skylake U
- Memory type : Intel HD Graphics
- Ethernet : 2x DDR4 sodimm 2133 MHz [up to 32 GB]
- Ethernet : 1x Intel I219LM gigabit ethernet (Intel I219V only for i3 6100)
- Ethernet : 1x Intel I211AT gigabit ethernet

Display:

- TFT type : 18.5" color TFT LED with LED Inverter
- Resolution : 1366x768 or 1920x1080 pixel
- Brightness : 300 or 350 cd/m² (typical)
- Contrast ratio : 1000:1 (typical)
- View angle : -170~170 (H); 178~170 (V)
- Max colours : 16.7 Millions
- Touch type : projected capacitive

Input / Output connectors:

- Serial ports : 3x RS-232; 1x RS-232/422/485 ports [-]
 - USB ports : 4x USB 3.0; 2x USB 2.0
 - Video output : 2x DP connectors
 - Ethernet : 2x RJ45 ports
 - Power connection : 24 VDC terminal block (1x 3-pins)
 - Power connection : 110 – 230 VAC standard cable
- [-] 2x RS-232 com ports are not present adding the optionals
2x RS-422/485 opto-isolated com ports

Support operating system:

- Windows 10 Enterprise LTSB 2016 [32/64 bit]
- Windows 10 Enterprise LTSC 2019 [32/64 bit]
- Linux (Ubuntu 14 or newer) and further distros

Expansion slots:

- 1x mini PCI-e
- 1x mini PCI-e / mSATA slot (Full Size) shared with SATA2 connector
- 2x SATA II connectors (raid 0/1 configurations only with i5 and i7 CPU)

Power specification:

- Rated input voltage : 24 VDC 110 – 230 VAC
- Input voltage limit: : 9.....36 VDC 90.....264 VAC
- Power consumption : 45 W (typical consumption)

Generic specifications:

- Dimension : 500x320x75 mm (L x H x W)
- Weight : 7,5 Kg
- Materials : 3 mm temperate glass (cover)
- Materials : galvanized (case)
- Cooling type : fanless
- Protection grade : IP 66 (frontal)
- Mounting type : panel mount with retaining clips
- Operating temperature : 0 °C - +50 °C (80% humidity, no condensing)

Order options:

- Storage: 2x HDD/SSD [*]
 - Storage: : 1x C-Fast (16 GB, 32GB) [*]
 - Memory module size: 4GB or 8GB DDR3L sodimm 2133 MHz
 - Additional Intel 82574L gigabit ethernet [mini PCI-e, full-size module]
 - Additional WI-Fi ethernet [mini PCI-e, half-size module]
 - Additional mini PCI-e modules on demand
 - Additional 2x RS-422/485 opto-isolated com ports [mini pci-e, full size] [-]
 - External USB 2.0 DVD-RW recorder
- [*] - Cannot be installed together