



Legend:

A - Audio Jack + HDMI Micro USB 2.0
B - USB 3.0 + USB 2.0
C - RJ45 LAN + DC In Jack
D - Docking connector
E - Micro SD + Micro Sim slot
F - RS232
G - RS485
H - USB 2.0

I - Front camera + Light sensor
J - Microphone
K - Speaker
L - Barcode Scanner [optional]
M - Rear camera
N - Scan button
O - Power button
P - Vol buttons
Q - Programmable button



System:

- CPU	: Intel® Atom® x5-Z8350
- Chipset	: Intel® Cherry Trail
- Graphic	: Intel® HD Graphics 400
- Memory type	: 1x DDR3L 4GB
- Storage capacity	: 64 GB eMMC [up to 128GB]
- Communication	: Wi-Fi support IEEE 802.11 a/b/g/n dual band : BT 4.0 : 3G (WCDMA, GSM, GPRS, EDGE)
- Navigation	: GPS, GLONASS
- Camera	: 2MP front, 5MP auto focus rear
- Sensors	: Built-in G-sensor, E-Compass, Gyroscope, Light-sensor

Display:

- TFT type	: 12.2" color TFT LCD with LED backlight
- Resolution	: 1920x1200 pixel
- Brightness	: 280 nit [anti-reflective coating]
- Max colours	: 16.7 millions
- Touch type	: Projected capacitive 10 point touchscreen, Gorilla Glass

Supported operating system:

- Windows 10 IoT Enterprise

Input / Output connectors:

- Serial ports	: 1x RS232, 1x RS485 port
- USB ports	: 1x USB 3.0; 2x USB 2.0; 1x Micro-USB ports
- Micro SD	: 1x Micro Secure Digital (SD) card slot
- SIM socket	: 1x Micro SIM card
- Video output	: 1x HDMI 1.4a mini connector
- Audio	: 1x audio jack 3.5mm: LINE OUT, headphone
- Ethernet	: 1x Gigabit port RJ45
- Power connector	: 1x DC jack
- Docking port	: 1x 12 pin docking connector
- Function keys	: 2x programmable; volume, power, scan

Power specification:

- Rated input voltage	: 5 VDC
- AC/DC Adapter	: 100-240V ~ 50/60 Hz; DC output: 5V, 3A
- Battery pack	: 3.7V, 12600 mAh removable

Order options:

- Barcode scanner	: 1D / 2D barcode scanner
- 4G	: LTE,WCDMA,HSDPA,HSUPA,EDGE,GSM,GPRS
- NFC	: support HF 13.56 MHz NFC
- Display	: anti-reflective coating

General specifications:

- Dimension	: 319,6x216x23,4 mm (L x H x W)
- Weight	: 1,5 Kg
- Protection grade	: IP 65
- Vibration	: mil STD 810G-514.7, Procedure I
- Drop test	: mil-STD-810G-516.6, Procedure IV
- Operating temperature	: -10°C to 50°C
- Humidity	: 95%, non-condensing

Accessories:

- Included	: Power supply : Handle : Hand strap : Table Bracket : USB 2.0 OTG cable, USB 2.0 A-to Micro B cable
<hr/>	
- Optional	: Car holder with or without DC in : Shoulder girdle : Belt strap : Keyboard